

SMARTDECK 30X30



DESCRIPTION	
Wooden tile made of Thermowood with an interlocking plastic base	

DATA & MEASURES	
Dimension	30 x 30 cm (1 mq = 11 pcs)
Thickness	2,5 cm
Material of the Base	HDPE
Material of the Surface	Thermowood®

TECHNICAL DATA		
	TEST	VALUE
PEFC certification	Valid	
Slip Resistance *	DIN 51130:2014-02	Class R10




* Definition of the slipperiness according to the classification DIN 51130: 2014-02 (BGR 181: 2003) ;values range from R9 (the worst) to R13 (the best). R10 corresponds to an average value of angle higher than 10° and up to 19°.

BENEFITS OF SMARTDECK
Easy to install and to remove thanks to its interlocking plastic base
Eco-Friendly plastic base made of 100% recyclable and recycled plastic
Suitable for all the project surfaces
Antislip
Made of ThermoWood®

BENEFITS OF THERMOWOOD®
High Dimensional Stability

High Durability
Mildew Resistant
The Thermo Treatment to which ThermoWood® is subjected, is obtained just with heat and steam, without using any chemical substance
Produced only with PEFC certified wood : the guarantee that our wood comes from areas subjected to strict rules about controlled deforestation
ThermoWood® is Resin Free

APPLICATION	
USE	Implementation or Restoration of outdoor floorings
IDEAL FOR	Gardens, balconies, terraces, patios, relax areas, walkways, pool side

INSTALLATION	
	
INSTALLATION TYPES	
Parallel Pattern 	Checkered Pattern 
<p>The installation is fast and easy. It does not require special tools.</p> <ol style="list-style-type: none"> 1. Place Smartdeck on a rigid and flat surface. 2. Install the elements exerting moderate pressure. Proceed horizontally in rows starting from left to right and from the top to the bottom. 3. Interlock the tiles following one of the installation patterns in the image here above, until the surface is totally covered. 4. Once the flooring is installed, proceed with the appropriate treatments for the maintenance. 	

CLEANING AND MAINTAINANCE
<p>Smartdeck, once installed, has to be treated with different products depending on the aesthetic preferences : if you want your decking to grey naturally, you should choose clear terrace oil which slows down and makes gradual the natural chromatic variation of the wood; we recommend to apply darker oils for higher protection and a substantial slowdown of the chromatic variation.</p> <p>CLEANING: We recommend to brush away dust and loose materials from the surface. Wash with water and a soft brush. Pressure washing is not recommended.</p> <p>MAINTAINANCE WITH OIL: Before oiling, brush away loose materials from the surface. Carefully wash the flooring using a detergent and wait for the complete drying. If the surface is covered by a clear film due to the previous treatment, remove it before continuing, brushing gently with soft brushes (as those made of sorghum or brass) and washing again the surface proceeding as above mentioned.</p> <p>GREYING AND RESTORING THE BROWN COLOUR: If left untreated, Smartdeck will be subjected to the oxidation process, with a progressive chromatic variation towards grey colour: this process is faster or slower depending on the intensity of the climatic conditions to which the flooring is subjected. If the surface has already turned to grey, it can be restored to its original colour by using</p> <p>BLACK SPOTS: Impurities in the air such as soot or pollen, or metallic dust can cause small black spots on the surface. In some cases the content of sulphate combine with water can colour the wood. Black spots can be prevented by treating the wood as mentioned in the paragraph about general maintainance. In the untreated surfaces of Smartdeck, the black spots normally disappear by themselves over the time, with the natural chromatic variation towards grey tones.</p> <p>The black spots can be removed by following these instructions: Carefully wash the surface using a proper detergent. Rinse and wait for the complete drying of the surface. Follow the instructions in the paragraph "MAINTAINANCE WITH OIL".</p>

MORE ABOUT SMARTDECK

- Thermowood is thermo treated to improve the durability and the stability of the wood. However slight bending or small deformation may occur even after the treatment because of the natural properties and the unique features of the wood.
- We recommend not to frame the flooring between walls and leave appropriate spaces for the natural expansion of the elements.
- If exposed to direct sunlight, Smartdeck can be subjected to the chromatic variation. To prevent this we recommend to treat the wood with the appropriate treatments mentioned in the paragraph "CLEANING AND MAINTAINANCE".

Pontarolo Engineering Spa

Via Clauzetto n° 20 Z.I.P.R. - 33078 San Vito al Tagliamento (PN) - Italy | T. +39 0434 857010 | F. +39 0434 857014 | info@onek.biz | www.onek.biz